



# Declaration of Performance



DoP-h10/0014  
(Issue 2.0)

1. *Product Type:* Dowel-type Timber Fasteners – Wood Screws
2. *Identification:* SDS
3. *Intended Use:* For structural timber products
4. *Manufacturer:* Simpson Strong-Tie Int. Ltd.  
For local branch addresses refer to [www.strongtie.eu](http://www.strongtie.eu)
5. *Authorised Representative:* N/A
6. *System of Assessment:* 3
- 7, 8. *Technical Specifications & Notified Bodies:*

	Name	No.	System of Assessment	Document Reference	EAD (ETAG) No. EN Standard
Technical Assessment	Simpson Strong-Tie	2209	3	ITTR-10/0014	EN14592:2012
Factory Production Control	Simpson Strong-Tie	-	-	-	-

9. Declared Performance:

Essential Characteristics	Performance	Technical Specification
<b>MECHANICAL STRENGTH &amp; STIFFNESS</b>		
Yield Moment for threaded section – $M_{y,k,thread}$ (KNmm)	17.4	EN 14592 clause 6.3.4.1 – 6.3.4.2 Tested to EN 409
Yield Moment for smooth section – $M_{y,k,smooth}$ (KNmm)	34.2	EN 14592 clause 6.3.4.1 – 6.3.4.2 Tested to EN 409
Withdrawal Parameter – $f_{ax,k}$ (N/mm <sup>2</sup> )	12.25	EN 14592 clause 6.3.4.3; Tested to EN 1382, characteristic timber density 350 kg/m <sup>3</sup>
Head Pull Through Parameter – $f_{head,k}$ (N/mm <sup>2</sup> )	21.5	EN 14592 clause 6.3.4.4; Tested to EN 1383, characteristic timber density 350 kg/m <sup>3</sup>
Characteristic Tensile Capacity – $f_{tens,k}$ (kN)	17.2	EN 14592 clause 6.3.4.4; Tested to EN 1383, characteristic timber density 350 kg/m <sup>3</sup>
Characteristic Torsional Strength – $f_{tor,k}$ (Nm)	16.8	EN 14592 clause 6.3.4.5; Tested to EN ISO 10666, characteristic timber density 350 kg/m <sup>3</sup>
<b>DURABILITY</b>		
Material	C20D	EN14592 clause 6.3.5; EN10016
Corrosion Protection	No Corrosion Protection Required	Service classes 1 & 2 to EN 1995-1-1; Table 4.1

10. The performance of the products identified in points 1. & 2. is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Laurent Versluysen**  
European Managing Director

(Sainte Gemme La Plaine, Fr. 16/03/2015)