



Declaration of Performance

SIMPSON**Strong-Tie**DoP-e07/0317
(Issue 3,0)

1. *Product Type:* Truss Connectors
2. *Identification:* SFN, SFM, SHLM, SHLS, SHH, SHB, GAF, SVI, PCAB46/2, PFA, PFP, TBE, TC, TCP, MJC, GS and ZYKLOP
3. *Intended Use:* Refer to ETA-07/0317 Section 1.2
4. *Manufacturer:* Simpson Strong-Tie Int. Ltd
For local branch addresses refer to www.strongtie.eu
5. *Authorised Representative:* N/A
6. *System of Assessment:* 2+
- 7, 8. *Technical Specifications & Notified Bodies:*

	Name	No.	System of Assessment	Document Reference	EAD (ETAG) No. EN Standard
Technical Assessment	BM TRADA Certification	-	2+	ETA-07/0317	ETAG015:2002
Factory Production Control	British Board of Agrément	0836	2+	0836-CPD-06/F007	-

9. Declared Performance:

Essential Characteristics	Performance	ETA Clause; EN Standard
Mechanical Resistance & Stability	ETA-07/0317	ETA Section 2.2, Annex 3
Reaction to Fire (Class)	A1	ETA Section 2.2; EN 13501-1
Resistance to Fire	NPD	-
Hygiene, Health and the Environment	No Dangerous Materials	ETA Section 2.2
Safety in Use	NPD	-
Protection against Noise	NPD	-
Energy, Economy & Heat Retention	NPD	-
Durability	Galvanised Steel: Z275, S235, S250 or S355 Stainless Steel: 1.4401 or 1.4404 Hot Dip Galvanised: $\geq 55\mu\text{m}$	ETA Sections 2.2, & Annex 2; Service Classes 1 & 2 to EN 1995-1-1; EN 10346; EN10149-2; EN10025 Service Classes 1,2 & 3 to EN 1995-1-1; EN 10088-2 EN 1461
Serviceability	NPD	-
Identification	Refer to Point 2. & ETA	ETA Sections 2.1 & Annex 2

(NPD – No Performance Determined)

10. The performance of the products identified in points 1. & 2. is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Laurent Versluysen
European Managing Director

(Sainte Gemme La Plaine, Fr. 27/06/2017)