



# Declaration of Performance



DoP-e11/0360  
(Issue 2.0)

1. *Product Type:* Bonded Anchor / Injection System
2. *Identification:* SET-XP
3. *Intended Use:* Refer to ETA-11/0360, Section 1.2
4. *Manufacturer:* Simpson Strong-Tie Int. Ltd  
For local branch addresses refer to [www.strongtie.eu](http://www.strongtie.eu)
5. *Authorised Representative:* N/A
6. *System of Assessment:* 1
- 7, 8. *Technical Specifications & Notified Bodies:*

	Name	No.	System of Assessment	Document Reference	EAD (ETAG) No. EN Standard
Technical Assessment	DIBt	-	1	ETA-11/0360	ETAG 001:2006, Parts 1 & 5, Option 1
Assessment and Verification of Constancy of Performance	Technical University Darmstadt	0756	1	0756-CPD-0453	-

9. Declared Performance:

Essential Characteristics	Performance	ETA Clause; EN or ISO Standard
Mechanical Resistance & Stability	ETA-11/0360 EOTA Technical Report TR 029	ETA Chapter 2, Annexes 4, 5, & 11 to 16
Reaction to Fire (Class)	NPD	-
Resistance to Fire	NPD	-
Hygiene, Health and the Environment	Refer to Product Label and Safety Data Sheet	EC 1907/2006 - REACH
Safety in Use	NPD	-
Protection against Noise	NPD	-
Energy, Economy & Heat Retention	NPD	-
Durability	Zinc Electroplated: $\geq 5 \mu\text{m}$ Hot Dip Galvanised: $> 40 \mu\text{m}$ Stainless Steel: A4-70, A4-80 & HCR	ETA Section 1.2 & Annex 3 EN ISO 4042; EN ISO 898-1 & -2 EN ISO 10684; EN ISO 898-1 & -2
Serviceability	Refer to ETA	EN 10088; EN ISO 3506-1 & -2 ETA Annexes 13 & 16
Identification	Refer to Point 2. & ETA	ETA Section 1.1 & Annexes 1, 2 & 3

(NPD – No Performance Determined)

10. The performance of the products identified in points 1. & 2. is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Laurent Versluysen**  
European Managing Director

(Sainte Gemme La Plaine, Fr. 01/07/2013)